

**SOUTH CAROLINA  
DEPARTMENT OF TRANSPORTATION**

Qualified Product Policy for  
Stabilizer Agents and Methods  
For Mixer Drum Wash Water  
Qualified Product List 32

In accordance with the SCDOT specifications, qualified stabilizer agents will be allowed in truck mixers and central mix drums that are of the normal rotational type. The purpose of using this type agent is to prevent mixer drum wash water from having to be dumped each night or over the weekend when mixing is finished for the day. This procedure is not intended for use in holding loads or portions of loads of concrete overnight; therefore, activator products are not necessary allowed when reloading the mixer following the use of a stabilizer.

In order to provide quality concrete that is not affected by the using of the agent, the methods listed on the Qualified Product List 32 for each product shall be strictly adhered to by the ready mix producer.

Other products may be added by the manufacturer furnishing complete information as to the products and its methods of use to:

Aly A. Hussein, PhD, P.E.  
Structural Materials Engineer  
SCDOT Office of Materials and Research  
PO Box 191  
Columbia, SC 29202  
(803) 737-6687  
Fax: (803) 737-6649  
Email: [husseinaa@scdot.org](mailto:husseinaa@scdot.org)

Complete the following form for each use:

## STABILIZATION OF CONCRETE WASH WATER

NOTE: Use the procedure outlined for the product being used for overnight or weekend stabilization of concrete wash water

[illegible]